

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

876809 - LED-DRV-20D2

Leddriver universeel

Package type: CT á 1 st



PRODUCT SPECIFICATIONS:

Type	Led driver
Type Led Driver	Universal
Model	Dynamic
Suitable for outdoor use	No
Type of dimming	1-10 V
Suitable for pulse button	Yes
Housing	Plastic housing
Output current (mA)	150 - 1200
Output power (W)	1 - 20
Degree of protection (IP)	IP20
Length (mm)	110
Width (mm)	52
Height (mm)	24
Constant current adjustable	Yes
Standard current setting (mA)	700
Setting change via	Dipswitches
Rated voltage (V)	180 - 240
Output voltage range	6 - 42
Voltage type	DC
Nominal rated frequency (Hz)	50 - 60
Dimrange (%)	0 - 100
Powerfactor	0.9
Temperature (°C)	-20 - +40
Housing color	Grey
With cable	No
Number of XPG LED 2,3W / 700mA	1 - 8
Number of XPG LED 2,3W / 350mA	1 - 12
Number of COB LED 3,3W / 350mA	1 - 4
Number of COB LED 6,3W / 700mA	1 - 3
Temperature protection	Yes
Short-circuit protection	Yes
Overcharge protection	Yes
SELV	Yes
Kema certified	Yes
(m)	5.5
(m)	3
(m)	4.5