


Tiny surfaced/pendant cover fitting

MODUS SBL1500, 600mm, white, prismatic cover, LED 830, 350mA DALI dimable, without switcher

Code: SBL1500SKN3/XB/DALI
EAN: 8596099058371



Vlastnosti svítidla

Product category:	Ceiling / wall luminaires	Degree of protection (IP):	IP20
Color housing:	White	Suitable for suspended mounting:	Yes
Material housing:	Aluminium	Suitable for wall mounting:	Yes
Suitable for surface mounting:	Yes	Suitable for ceiling mounting:	Yes
Made in Czech republic:	Yes		

Světelný zdroj

Lamp type:	LED not exchangeable	Effective luminous flux (lm):	1500
System power (W):	15	Luminaire efficacy (lm/W):	100
Color temperature (K):	4000	Color rendering index CRI:	80-89
Rated life time L80/B50 (h):	80000	With lamp:	Yes
Colour of light:	White		
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)		

Optický systém

Optical system:	KN	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, structured
Radiation angle:	Extreme wide beam >80°		

Rozměry

Length (mm):	605	Width (mm):	42
Height/depth (mm):	45	Built-in length (mm):	490
Size version:	S	Weight (kg):	1

Elektrické vlastnosti

Protection class:	I	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220...240
Control gear included:	Yes	Dimming DALI:	Yes