

Pendant direct/indirect luminaire with aluminium frame



MODUS ART5000, direct/indirect, pendant, LED 830, DALI - 2 chanel, rectangle 200x1210mm, decor A, surfaced gear box

Code: ART5000DI2M3GPNA/DALI
EAN: 8596099066192



Vlastnosti svítidla

Product category:	Pendant luminaire	Degree of protection (IP):	IP20
Color housing:	Grey	Material housing:	Aluminium
Suspension supplied with the product:	Yes	Made in Czech republic:	Yes

Světelný zdroj

Lamp type:	LED not exchangeable	Effective luminous flux (lm):	4800
System power (W):	50	Luminaire efficacy (lm/W):	96
Color temperature (K):	3000	Rated life time L80/B50 (h):	80000
With lamp:	Yes	Colour of light:	White
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)		

Optický systém

Light outlet:	Direct/indirect	Light sharing:	Symmetric
Material cover:	Plastic, structured		

Rozměry

Length (mm):	1210	Width (mm):	200
Height/depth (mm):	22	Pendant length (mm):	150...2000
Size version:	M	Weight (kg):	7

Elektrické vlastnosti

Protection class:	I	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Direct-/indirect proportion separately controllable:	Yes
Nominal voltage (V):	220...240	Control gear included:	Yes
Dimming DALI:	Yes		