

# TUBE R



<b>SKU</b>	: 2.011E0A930004500000
<b>Beam angle</b>	: 45°
<b>Adjustability</b>	: 350° rotational and 90° tiltable
<b>CCT</b>	: 3000K
<b>CRI</b>	: (RA) >90
<b>Chromaticity tolerance</b>	: 3
<b>Luminous flux</b>	: 3000Lm
<b>Connected load</b>	: 30W
<b>System efficiency</b>	: 100Lm/W
<b>Lifetime/Failure rate</b>	: >100000h/L80B20,>50000h/L90B50
<b>Electrical Safety Class</b>	: Class I
<b>Optic</b>	: Facet anodized aluminum reflector
<b>Color housing</b>	: White (RAL 9003)
<b>Material</b>	: Die Cast Aluminum
<b>Mains voltage</b>	: 220-240V / 50-60Hz
<b>Max. ambient temperature</b>	: 35°C
<b>Ingress protection</b>	: IP20
<b>Energy rating (EEC)</b>	: A++
<b>Installation</b>	: Track mounted
<b>Net. weight</b>	: 1.1Kg
<b>Warranty</b>	: 5 years

All rated values @ ambient temperature of 25° C. Electric and photometric values are initially subject to a tolerance of +/- 10%. Tolerance of color temperature +/- 150K. Technical data can change without prior notice.



