

## Fire protection cavity wall box



BRANDSCHUTZ



### One-gang box HWD 90

- for fire-protection walls EI30 - EI20
- also for installation shafts/installation channels I30 - I90

|   |                |
|---|----------------|
| <b>Order number:</b>  | <b>9463-01</b> |
| EAN:  | 4013456531659  |
| Depth   | 44 mm          |
| Cut hole Ø  | 74 mm          |
| For panel thickness   | 7 - 40 mm      |
| Combination distance through single separation of the pre-embossed edge | 71 mm          |
| Cable entries of up to Ø 11.5 mm  | 2              |
| DIBt approval   | Z-19.21-1788   |
| Halogen-free  |                |
| for sound insulation walls up to  | 77 dB          |
| Packaging inner/dispatch  | 10/100         |
| Price/1 ST  | 11.70€         |
| Price group   | 190            |

HWD 90 cavity wall boxes for EI30-EI120 fire-protection walls ensure certified and fire-protection compliant electrical installation. Intelligent AFS technology reacts immediately to fire and heat and automatically seals the installation opening. This guarantees the fire resistance class of the fire-protection wall and secures escape routes. Use in all fire-protection walls and the fire-resistance duration of up to 120 minutes ensures maximum flexibility, even when the planning is changed. At the same time, it also maintains the wall's sound insulation requirements.

- For EI30-EI120 fire-protection walls
- Maintains the wall's sound insulation protection
- Also suitable for retrofitting
- With fire-protection cover can be used as a junction box
- Also for directly opposing installation

