

Fire protection cavity wall box



BRANDSCHUTZ



One-gang junction box HWD 90

- for fire-protection walls EI30 - EI20
- also for installation shafts/installation channels I30 - I90

Order number:	9464-01
EAN:	4013456531666
Depth	54,5 mm
Cut hole Ø	74 mm
For panel thickness	7 - 40 mm
Combination distance through single separation of the pre-embossed edge	71 mm
Cable entries of up to Ø 11.5 mm	4
alternatively cable entry for three-phase alternating current of up to 5 x 2.5 mm possible	
Support connectors for each package	5
DIBt approval	Z-19.21-1788
Halogen-free	
for sound insulation walls up to	77 dB
Packaging inner/dispatch	10/100
Price/1 ST	13.90€
Price group	190

HWD 90 cavity wall boxes for EI30-EI120 fire-protection walls ensure certified and fire-protection compliant electrical installation. Intelligent AFS technology reacts immediately to fire and heat and automatically seals the installation opening. This guarantees the fire resistance class of the fire-protection wall and secures escape routes. Use in all fire-protection walls and the fire-resistance duration of up to 120 minutes ensures maximum flexibility, even when the planning is changed. At the same time, it also maintains the wall's sound insulation requirements.

- For EI30-EI120 fire-protection walls
- Maintains the wall's sound insulation protection
- Also suitable for retrofitting
- With fire-protection cover can be used as a junction box
- Also for directly opposing installation

