

Raumakustik • Bauphysik  
Medientechnik • Schallschutz  
VMPA Schallschutzprüfstelle nach DIN 4109  
Messstelle nach § 29b  
Bundes-Immissionsschutzgesetz

D-51465 Bergisch Gladbach  
Lichtenweg 15-17  
info@graner-ingenieure.de  
www.graner-ingenieure.de

Zentrale: +49 (0) 2202 936 30-0  
Immission: +49 (0) 2202 936 30-10  
Fax: +49 (0) 2202 936 30-30

Unternehmensform: GmbH  
Geschäftsführung:  
Brigitte Graner  
Bernd Graner-Sommer  
Amtsgericht Köln • HRB 45768  
Ru A0388-II-1310

Gräf (Cert. Eng.), extension: -18

13.Okt.2010

### TEST CERTIFICATE

• Determination of sound insulation  $R'_w$  in accordance with DIN EN ISO 140-3 / 717-1 •

Test object: Influence of switch and socket boxes (cavity wall boxes)  
integrated in lightweight walls on sound insulation


Applicant: Kaiser GmbH & Co. KG  
Ramsloh 4  
58579 Schalksmühle


Test certificate no.: A0388 - II

Drawn up on: 13 Oktober 2010



  
(GRANER+PARTNER)

  
(head of testing centre)

  
(measurement engineer)

**Contents**

	Page
1. General provisions	3
2. System description of test material / test set-up	3
3. Sound insulation test	4
4. Measurement technique	5
5. Measurement and analysis specifications	5
6. Measurement results	6

**Appendices**

Evaluation diagrams for constructional sound reduction indices

## 1. **General provisions**

The sound reduction index of the test material is determined in accordance with  
DIN EN ISO 140 / 717.

Graner + Partner (G + P) is entitled to publish the test certificate. This also applies to any translation of the certificate into another language. Reproduction by the client is permissible. Transmission to a third party or parties is restricted to either the title page alone or the entire test certificate. No individual parts of the certificate may be passed on. If the test certificate is to be used for advertising purposes or publications, G + P will receive a specimen copy.

The test certificate will remain valid for as long as the manufacturer guarantees continued use of the materials tested with the same properties and structures.

### **Revocation of test certificate**

The test certificate may be revoked by G + P if the conditions for its issue are no longer fulfilled. This applies in particular if materials or structural designs have been altered, so that the product no longer corresponds to the version tested.

## 2. **System description of test material / test set-up**

The aim of the examinations conducted here was to ascertain the extent to which cavity wall boxes designed to accommodate light switches, sockets and other similar devices installed in lightweight partition walls compromise the sound insulation of those walls.

To this end, a lightweight wall with a metal frame was installed in the test stand for constructional acoustics.

### **Structure of lightweight wall**

- gypsum plasterboard panelling, Knauf, 12.5 mm silent board, 12.5 mm diamant, 12.5 mm silent bard, on CW 100 metal frame
- mineral fibre insulating material packed into frame, thickness 80 mm
- ventilation space
- frame and panelling as above
- overall structure approx. 485 mm

In the first stage, the sound insulation of the construction was measured.

Following that, the switch and socket boxes were installed in pairs in the partition wall, each box in a pair being placed directly opposite the other. The insulating material in the wall cavity between the switch and socket boxes was completely removed. Empty conduit with cables was introduced into each box. The conduit was closed off by means of a plug. The boxes were equipped with devices or fitted with a cover plate.

### 3. **Sound insulation test**

The size of the test surface, i.e. the area of the partition wall element, was 11.7 m<sup>2</sup>. In the evaluation of the constructional sound reduction indices, the sound insulation was determined with reference to this test surface.

The following individual measurements were carried out:

- measurement of the sound insulation of the lightweight wall element without any installations
- measurement of the sound insulation after the integration of installations as follows:
  - 3 x fire protection box HWD 90, type 9464-01, with fire protection cover plate type 1184-01
  - as above, but with device
  - as above, but with 3 x fivefold combination with device, type 9464-01

each member of a pair being directly opposite the other.

Between the boxes the insulating material was completely removed, and the boxes were connected up with one another using empty conduit with cables inserted.

**4. Measurement technique**

Cortex Instruments	Spectrum Analyser, Type NC10 Free-field microphone 221 Pre-amplifier MV203
Norsonic	Amplifier, Type 235
Behr & Obermeyer	Loudspeakers

**5. Measurement and analysis specifications**

DIN EN ISO 140:

Measurement of sound insulation in buildings and of building elements  
Part 3: Laboratory measurement of airborne sound insulation of elements

DIN EN ISO 717-1:

Rating of sound insulation in buildings and of building elements –  
Part 1: Airborne sound insulation

The test sound used was noise, filtered by means of third-octave filters on the transmission and receiving sides in accordance with DIN 45652.

The measurements were carried out with 2 loudspeakers and 2 positions each on the microphone swivel unit (4 measurement sequences each on both the transmission and the receiving side).

The sound reduction index is calculated from the measurement values as follows:

$$R' = L_1 - L_2 + 10 \log S/A, \quad A = 0.16 \cdot V/T$$

Key to symbols used in formula:

$R'$	=	sound reduction index as per DIN EN ISO 140
$L_1$	=	sound pressure level in transmission room
$L_2$	=	sound pressure level in receiving room
$S$	=	surface area of test wall
$A$	=	equivalent sound absorption surface area of transmission room, determined from measurements of reverberation time
$V$	=	volume of receiving room
$T$	=	reverberation time in receiving room

**6. Measurement results**

The measurements thus carried out resulted in the following single sound insulation values (see also Appendices 1 - 2):

Appendix 1	Sound insulation of partition wall element without fittings	$R_w = 77 \text{ dB}$
Appendix 2	Sound reduction index with fittings 3 x fire protection box HWD 90, type 9464-01 with fire protection cover plate type 1184-01 Each member of a pair being directly opposite the other	$R_w = 77 \text{ dB}$
Appendix 3	as above but with devices	$R_w = 77 \text{ dB}$
Appendix 4	As above, but 3 x fivefold combination with devices	$R_w = 77 \text{ dB}$

These single values are already enough to show that the installation of the combined wall and joint boxes does not cause any weakening of the wall construction in terms of its constructional acoustics. It can, moreover, also be seen from the comparative diagram in Appendix 5 that no relevant weakening occurs in individual frequency ranges either.



No part of this test certificate may be reproduced without the prior approval of Graner + Partner Ingenieure GmbH. This test certificate consists of 6 pages and Appendices 1-5.

<b>Sound reduction index, as per ISO 140-3: 1995</b>		<b>Appendix: 1</b>
		<b>Order no.: A0388</b>
<b>client:</b> Kaiser GmbH & Co. KG, Ramsloh 4, 58579 Schalksmühle		<b>Test date:</b> 24.08.2010

<b>Objekt:</b>  sound insulation and fire protection boxes Kaiser GmbH device connection Boxes	<b>Structure:</b>  Lightweight partition wall, separate framework 2 x CW100 Planking on both sides made of Knauf gypsum boards Each structure: 12,5 mm silent board, 12,5 mm diamant, 12,5 mm silent board ventilation space with mineral fibre insulating material Knauf TP115 2 x 80 mm, overall structure approx. 485 mm
--	--

**Conditions**

**transmit**  
 volume V = 53,6/61,7 m³

Type: laboratory 1 / laboratory 2  
 Location: Ground floor

**receive**  
 volume V = 61,7/53,6 m³

Type: Laboratory 2 / Laboratory 1  
 Location: Ground floor

surface area: 11,7 m²

Freq.: [Hz]	R' [dB]	shifted reference curve
50	48,0	
63	50,2	
80	50,6	
100	55,7	58,0
125	60,4	61,0
160	58,9	64,0
200	63,2	67,0
250	66,7	70,0
315	70,8	73,0
400	71,1	76,0
500	74,8	77,0
630	78,8	78,0
800	84,7	79,0
1000	83,8	80,0
1250	87,4	81,0
1600	90,6	81,0
2000	89,5	81,0
2500	89,5	81,0
3150	86,7	81,0
4000	83,5	
5000	79,0	

Building sound insulation index R

Evaluation as per ISO 717-1	C <sub>50-3150</sub> = -2 dB	C <sub>50-5000</sub> = -2 dB	C <sub>100-5000</sub> = -1 dB
<b>R'w (C,Ctr) = 77 (-1;-6) dB</b>	C <sub>tr50-3150</sub> = -11 dB	C <sub>tr50-5000</sub> = -11 dB	C <sub>tr100-5000</sub> = -6 dB

VMPA - recognized sound insulation testing authority as per DIN 4109 Test centre as per §§ 26, 28 BImSchG (German Federal Immission Control)	<b>GRANER + PARTNER</b> <b>I N G E N I E U R E</b> Raumakustik Tontechnik Bauphysik Schallschutz 51465 Bergisch Gladbach
--	---

**date:** 30.08.2010 **Compiled by:** Dipl. Ing. U. Gräf

<b>Sound reduction index, as per ISO 140-3: 1995</b>		Appendix: 2																																																																		
		Order no.: A0388																																																																		
client: Kaiser GmbH & Co. KG, Ramsloh 4, 58579 Schalksmühle	Test date: 24.08.2010																																																																			
<b>Objekt:</b>	<b>Aufbau des Prüfgegenstandes</b>																																																																			
sound insulation and fire protection boxes Kaiser GmbH device connection Boxes	Lightweight partition wall, separate framework 2 x CW100 Planking on both sides made of Knauf gypsum boards Each structure: 12,5 mm silent board, 12,5 mm diamant, 12,5 mm silent board ventilation space with mineral fibre insulating material Knauf TP115 2 x 80 mm, overall structure approx. 485 mm																																																																			
<b>Conditions</b>																																																																				
<b>transmit</b> volume V = 53,6/61,7 m³	with 3 x fire protection box HWD90, Typ 9464-01 each member of a pair being directly opposite the other with fire protection cover plate type 1184-01 and cables inserted																																																																			
Type: laboratory 1 / laboratory 2 Location: Ground floor																																																																				
<b>receive</b> volume V = 61,7/53,6 m³																																																																				
Type: Laboratory 2 / Laboratory 1 Location: Ground floor																																																																				
surface area: 11,7 m²																																																																				
<table border="1"> <thead> <tr> <th>Freq.: [Hz]</th><th>R' [dB]</th><th>shifted reference curve</th></tr> </thead> <tbody> <tr><td>50</td><td>48,0</td><td></td></tr> <tr><td>63</td><td>47,9</td><td></td></tr> <tr><td>80</td><td>50,0</td><td></td></tr> <tr><td>100</td><td>55,0</td><td>58,0</td></tr> <tr><td>125</td><td>60,8</td><td>61,0</td></tr> <tr><td>160</td><td>58,6</td><td>64,0</td></tr> <tr><td>200</td><td>62,4</td><td>67,0</td></tr> <tr><td>250</td><td>66,3</td><td>70,0</td></tr> <tr><td>315</td><td>70,7</td><td>73,0</td></tr> <tr><td>400</td><td>71,0</td><td>76,0</td></tr> <tr><td>500</td><td>75,0</td><td>77,0</td></tr> <tr><td>630</td><td>80,5</td><td>78,0</td></tr> <tr><td>800</td><td>84,8</td><td>79,0</td></tr> <tr><td>1000</td><td>84,0</td><td>80,0</td></tr> <tr><td>1250</td><td>87,0</td><td>81,0</td></tr> <tr><td>1600</td><td>90,2</td><td>81,0</td></tr> <tr><td>2000</td><td>90,2</td><td>81,0</td></tr> <tr><td>2500</td><td>89,7</td><td>81,0</td></tr> <tr><td>3150</td><td>86,9</td><td>81,0</td></tr> <tr><td>4000</td><td>83,6</td><td></td></tr> <tr><td>5000</td><td>79,2</td><td></td></tr> </tbody> </table>	Freq.: [Hz]	R' [dB]	shifted reference curve	50	48,0		63	47,9		80	50,0		100	55,0	58,0	125	60,8	61,0	160	58,6	64,0	200	62,4	67,0	250	66,3	70,0	315	70,7	73,0	400	71,0	76,0	500	75,0	77,0	630	80,5	78,0	800	84,8	79,0	1000	84,0	80,0	1250	87,0	81,0	1600	90,2	81,0	2000	90,2	81,0	2500	89,7	81,0	3150	86,9	81,0	4000	83,6		5000	79,2		<div> <div>— : R'</div> <div>— : shifted reference curve as per ISO 717</div> </div>	
Freq.: [Hz]	R' [dB]	shifted reference curve																																																																		
50	48,0																																																																			
63	47,9																																																																			
80	50,0																																																																			
100	55,0	58,0																																																																		
125	60,8	61,0																																																																		
160	58,6	64,0																																																																		
200	62,4	67,0																																																																		
250	66,3	70,0																																																																		
315	70,7	73,0																																																																		
400	71,0	76,0																																																																		
500	75,0	77,0																																																																		
630	80,5	78,0																																																																		
800	84,8	79,0																																																																		
1000	84,0	80,0																																																																		
1250	87,0	81,0																																																																		
1600	90,2	81,0																																																																		
2000	90,2	81,0																																																																		
2500	89,7	81,0																																																																		
3150	86,9	81,0																																																																		
4000	83,6																																																																			
5000	79,2																																																																			
Evaluation as per ISO 717-1 <b>R'w (C,Ctr) = 77 (-2;-7) dB</b>																																																																				
<table> <tr> <td>C<sub>50-3150</sub> = -3 dB</td> <td>C<sub>50-5000</sub> = -2 dB</td> <td>C<sub>100-5000</sub> = -1 dB</td> </tr> <tr> <td>C<sub>tr50-3150</sub> = -12 dB</td> <td>C<sub>tr50-5000</sub> = -12 dB</td> <td>C<sub>tr100-5000</sub> = -7 dB</td> </tr> </table>			C <sub>50-3150</sub> = -3 dB	C <sub>50-5000</sub> = -2 dB	C <sub>100-5000</sub> = -1 dB	C <sub>tr50-3150</sub> = -12 dB	C <sub>tr50-5000</sub> = -12 dB	C <sub>tr100-5000</sub> = -7 dB																																																												
C <sub>50-3150</sub> = -3 dB	C <sub>50-5000</sub> = -2 dB	C <sub>100-5000</sub> = -1 dB																																																																		
C <sub>tr50-3150</sub> = -12 dB	C <sub>tr50-5000</sub> = -12 dB	C <sub>tr100-5000</sub> = -7 dB																																																																		
VMPA - recognized sound insulation testing authority as per DIN 4109 Test centre as per §§ 26, 28 BImSchG (German Federal Immission Control)	<b>GRANER + PARTNER</b> INGENIEURE Raumakustik Tontechnik Bauphysik Schallschutz 51465 Bergisch Gladbach																																																																			
date: 30.08.2010	Compiled by: Dipl. Ing. U. Gräf																																																																			



<b>Sound reduction index, as per ISO 140-3: 1995</b>		<b>Appendix: 3</b>
		<b>Order no.: A0388</b>
<b>client:</b> Kaiser GmbH & Co. KG, Ramsloh 4, 58579 Schalksmühle		<b>Test date:</b> 24.08.2010

<b>Objekt:</b>  sound insulation and fire protection boxes Kaiser GmbH device connection Boxes  <b>Conditions</b>  <b>transmit</b> volume V = 53,6/61,7 m³  Type: laboratory 1 / laboratory 2 Location: Ground floor  <b>receive</b> volume V = 61,7/53,6 m³  Type: Laboratory 2 / Laboratory 1 Location: Ground floor  surface area: 11,7 m²	<b>Aufbau des Prüfgegenstandes</b>  Lightweight partition wall, separate framework 2 x CW100 Planking on both sides made of Knauf gypsum boards Each structure: 12,5 mm silent board, 12,5 mm diamant, 12,5 mm silent board ventilation space with mineral fibre insulating material Knauf TP115 2 x 80 mm, overall structure approx. 485 mm  with 3 x fire protection box HWD90, Typ 9464-01 each member of a pair being directly opposite the other with device and cables inserted
---	--

Freq.: [Hz]	R' [dB]	shifted reference curve
50	47,8	
63	48,3	
80	49,8	
100	54,6	58,0
125	60,6	61,0
160	58,5	64,0
200	62,5	67,0
250	66,3	70,0
315	70,9	73,0
400	71,3	76,0
500	75,3	77,0
630	80,6	78,0
800	85,0	79,0
1000	84,5	80,0
1250	87,8	81,0
1600	90,3	81,0
2000	89,9	81,0
2500	90,3	81,0
3150	86,9	81,0
4000	83,7	
5000	79,2	

↑  
Building sound insulation index R  
↓

frequency (Hz)

Evaluation as per ISO 717-1 <b><math>R'_w (C, C_{tr}) = 77 (-2; -7) \text{ dB}</math></b>	$C_{50-3150} = -3 \text{ dB}$ $C_{tr50-3150} = -12 \text{ dB}$	$C_{50-5000} = -2 \text{ dB}$ $C_{tr50-5000} = -12 \text{ dB}$	$C_{100-5000} = -1 \text{ dB}$ $C_{tr100-5000} = -7 \text{ dB}$
--	---	---	--

VMPA - recognized sound insulation testing authority as per DIN 4109 Test centre as per §§ 26, 28 BImSchG (German Federal Immission Control)	<b>GRANER + PARTNER</b> <b>I N G E N I E U R E</b> Raumakustik Tontechnik Bauphysik Schallschutz 51465 Bergisch Gladbach
--	---

**date:** 30.08.2010    **Compiled by:** Dipl. Ing. U. Gräf

<b>Sound reduction index, as per ISO 140-3: 1995</b>		<b>Appendix: 4</b>
		<b>Order no.: A0388</b>
<b>client:</b> Kaiser GmbH & Co. KG, Ramsloh 4, 58579 Schalksmühle		<b>Test date:</b> 24.08.2010

<b>Objekt:</b>  sound insulation and fire protection boxes Kaiser GmbH device connection Boxes  <b>Conditions</b>  <b>transmit</b> volume V = 53,6/61,7 m³  Type: laboratory 1 / laboratory 2 Location: Ground floor  <b>receive</b> volume V = 61,7/53,6 m³  Type: Laboratory 2 / Laboratory 1 Location: Ground floor  surface area: 11,7 m²	<b>Aufbau des Prüfgegenstandes</b>  Lightweight partition wall, separate framework 2 x CW100 Planking on both sides made of Knauf gypsum boards Each structure: 12,5 mm silent board, 12,5 mm diamant, 12,5 mm silent board ventilation space with mineral fibre insulating material Knauf TP115 2 x 80 mm, overall structure approx. 485 mm  with 3 x fivefold combination fire protection box HWD90, Typ 946- each member of a pair being directly opposite the other with device and cables inserted
---	--

<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>Freq.: [Hz]</th> <th>R' [dB]</th> <th>shifted reference curve</th> </tr> </thead> <tbody> <tr><td>50</td><td>49,2</td><td></td></tr> <tr><td>63</td><td>47,9</td><td></td></tr> <tr><td>80</td><td>50,1</td><td></td></tr> <tr><td>100</td><td>55,1</td><td>58,0</td></tr> <tr><td>125</td><td>59,8</td><td>61,0</td></tr> <tr><td>160</td><td>59,1</td><td>64,0</td></tr> <tr><td>200</td><td>62,4</td><td>67,0</td></tr> <tr><td>250</td><td>65,6</td><td>70,0</td></tr> <tr><td>315</td><td>71,2</td><td>73,0</td></tr> <tr><td>400</td><td>71,3</td><td>76,0</td></tr> <tr><td>500</td><td>74,7</td><td>77,0</td></tr> <tr><td>630</td><td>79,7</td><td>78,0</td></tr> <tr><td>800</td><td>85,6</td><td>79,0</td></tr> <tr><td>1000</td><td>84,3</td><td>80,0</td></tr> <tr><td>1250</td><td>86,6</td><td>81,0</td></tr> <tr><td>1600</td><td>90,2</td><td>81,0</td></tr> <tr><td>2000</td><td>90,3</td><td>81,0</td></tr> <tr><td>2500</td><td>90,1</td><td>81,0</td></tr> <tr><td>3150</td><td>86,9</td><td>81,0</td></tr> <tr><td>4000</td><td>83,5</td><td></td></tr> <tr><td>5000</td><td>79,2</td><td></td></tr> </tbody> </table>	Freq.: [Hz]	R' [dB]	shifted reference curve	50	49,2		63	47,9		80	50,1		100	55,1	58,0	125	59,8	61,0	160	59,1	64,0	200	62,4	67,0	250	65,6	70,0	315	71,2	73,0	400	71,3	76,0	500	74,7	77,0	630	79,7	78,0	800	85,6	79,0	1000	84,3	80,0	1250	86,6	81,0	1600	90,2	81,0	2000	90,3	81,0	2500	90,1	81,0	3150	86,9	81,0	4000	83,5		5000	79,2		<div style="text-align: right; margin-bottom: 10px;">       — : R'        — : shifted reference curve as per ISO 717     </div>
Freq.: [Hz]	R' [dB]	shifted reference curve																																																																	
50	49,2																																																																		
63	47,9																																																																		
80	50,1																																																																		
100	55,1	58,0																																																																	
125	59,8	61,0																																																																	
160	59,1	64,0																																																																	
200	62,4	67,0																																																																	
250	65,6	70,0																																																																	
315	71,2	73,0																																																																	
400	71,3	76,0																																																																	
500	74,7	77,0																																																																	
630	79,7	78,0																																																																	
800	85,6	79,0																																																																	
1000	84,3	80,0																																																																	
1250	86,6	81,0																																																																	
1600	90,2	81,0																																																																	
2000	90,3	81,0																																																																	
2500	90,1	81,0																																																																	
3150	86,9	81,0																																																																	
4000	83,5																																																																		
5000	79,2																																																																		

Evaluation as per ISO 717-1 <b>R'w (C,Ctr) = 77 (-2;-7) dB</b>	C50-3150 = -3 dB Ctr50-3150 = -12 dB	C50-5000 = -2 dB Ctr50-5000 = -12 dB	C100-5000 = -1 dB Ctr100-5000 = -7 dB
---	---	---	--

VMPA - recognized sound insulation testing authority as per DIN 4109 Test centre as per §§ 26, 28 BImSchG (German Federal Immission Control)	<b>GRANER + PARTNER</b> <b>I N G E N I E U R E</b> Raumakustik Tontechnik Bauphysik Schallschutz 51465 Bergisch Gladbach
<b>date:</b> 30.08.2010 <b>Compiled by:</b> Dipl. Ing. U. Gräf	

Comparison of sound insulation index						Appendix:	5																																																																																																														
						Order no.:	A0388																																																																																																														
client: Kaiser GmbH & Co. KG, Ramsloh 4, 58579 Schalksmühle						Test date:	24.08.2010																																																																																																														
Objekt:																																																																																																																					
sound insulation and fire protection boxes Kaiser GmbH device connection Boxes				Lightweight partition wall, separate framework 2 x CW100 Planking on both sides made of Knauf gypsum boards Each structure: 12,5 mm silent board, 12,5 mm diamant, 12,5 mm silent board ventilation space with mineral fibre insulating material Knauf TP115 2 x 80 mm, overall structure approx. 485 mm  base wall with different boxes																																																																																																																	
<table><tr><th>frequ. [Hz]</th><th>range 1</th><th>range 2</th><th>range 3</th><th>range 4</th></tr><tr><td>50</td><td>48,0</td><td>47,8</td><td>48,0</td><td>49,2</td></tr><tr><td>63</td><td>50,2</td><td>48,3</td><td>47,9</td><td>47,9</td></tr><tr><td>80</td><td>50,6</td><td>49,8</td><td>50,0</td><td>50,1</td></tr><tr><td>100</td><td>55,7</td><td>54,6</td><td>55,0</td><td>55,1</td></tr><tr><td>125</td><td>60,4</td><td>60,6</td><td>60,8</td><td>59,8</td></tr><tr><td>160</td><td>58,9</td><td>58,5</td><td>58,6</td><td>59,1</td></tr><tr><td>200</td><td>63,2</td><td>62,5</td><td>62,4</td><td>62,4</td></tr><tr><td>250</td><td>66,7</td><td>66,3</td><td>66,3</td><td>65,6</td></tr><tr><td>315</td><td>70,8</td><td>70,9</td><td>70,7</td><td>71,2</td></tr><tr><td>400</td><td>71,1</td><td>71,3</td><td>71,0</td><td>71,3</td></tr><tr><td>500</td><td>74,8</td><td>75,3</td><td>75,0</td><td>74,7</td></tr><tr><td>630</td><td>78,8</td><td>80,6</td><td>80,5</td><td>79,7</td></tr><tr><td>800</td><td>84,7</td><td>85,0</td><td>84,8</td><td>85,6</td></tr><tr><td>1000</td><td>83,8</td><td>84,5</td><td>84,0</td><td>84,3</td></tr><tr><td>1250</td><td>87,4</td><td>87,8</td><td>87,0</td><td>86,6</td></tr><tr><td>1600</td><td>90,6</td><td>90,3</td><td>90,2</td><td>90,2</td></tr><tr><td>2000</td><td>89,5</td><td>89,9</td><td>90,2</td><td>90,3</td></tr><tr><td>2500</td><td>89,5</td><td>90,3</td><td>89,7</td><td>90,1</td></tr><tr><td>3150</td><td>86,7</td><td>86,9</td><td>86,9</td><td>86,9</td></tr><tr><td>4000</td><td>83,5</td><td>83,7</td><td>83,6</td><td>83,5</td></tr><tr><td>5000</td><td>79,0</td><td>79,2</td><td>79,2</td><td>79,2</td></tr></table>				frequ. [Hz]	range 1	range 2	range 3	range 4	50	48,0	47,8	48,0	49,2	63	50,2	48,3	47,9	47,9	80	50,6	49,8	50,0	50,1	100	55,7	54,6	55,0	55,1	125	60,4	60,6	60,8	59,8	160	58,9	58,5	58,6	59,1	200	63,2	62,5	62,4	62,4	250	66,7	66,3	66,3	65,6	315	70,8	70,9	70,7	71,2	400	71,1	71,3	71,0	71,3	500	74,8	75,3	75,0	74,7	630	78,8	80,6	80,5	79,7	800	84,7	85,0	84,8	85,6	1000	83,8	84,5	84,0	84,3	1250	87,4	87,8	87,0	86,6	1600	90,6	90,3	90,2	90,2	2000	89,5	89,9	90,2	90,3	2500	89,5	90,3	89,7	90,1	3150	86,7	86,9	86,9	86,9	4000	83,5	83,7	83,6	83,5	5000	79,0	79,2	79,2	79,2	<p>range 1: base wall without boxes, 77 dB</p> <p>range 2: with single fire protection boxes HWD90 with device, 77 dB</p> <p>range 3: with single fire protection boxes HWD90 with cover plate, 77 dB</p> <p>range 4: with fivefold fire protection boxes HWD90 with device, 77 dB</p>			
frequ. [Hz]	range 1	range 2	range 3	range 4																																																																																																																	
50	48,0	47,8	48,0	49,2																																																																																																																	
63	50,2	48,3	47,9	47,9																																																																																																																	
80	50,6	49,8	50,0	50,1																																																																																																																	
100	55,7	54,6	55,0	55,1																																																																																																																	
125	60,4	60,6	60,8	59,8																																																																																																																	
160	58,9	58,5	58,6	59,1																																																																																																																	
200	63,2	62,5	62,4	62,4																																																																																																																	
250	66,7	66,3	66,3	65,6																																																																																																																	
315	70,8	70,9	70,7	71,2																																																																																																																	
400	71,1	71,3	71,0	71,3																																																																																																																	
500	74,8	75,3	75,0	74,7																																																																																																																	
630	78,8	80,6	80,5	79,7																																																																																																																	
800	84,7	85,0	84,8	85,6																																																																																																																	
1000	83,8	84,5	84,0	84,3																																																																																																																	
1250	87,4	87,8	87,0	86,6																																																																																																																	
1600	90,6	90,3	90,2	90,2																																																																																																																	
2000	89,5	89,9	90,2	90,3																																																																																																																	
2500	89,5	90,3	89,7	90,1																																																																																																																	
3150	86,7	86,9	86,9	86,9																																																																																																																	
4000	83,5	83,7	83,6	83,5																																																																																																																	
5000	79,0	79,2	79,2	79,2																																																																																																																	
VMPA - recognized sound insulation testing authority as per DIN 4109 Test centre as per §§ 26, 28 BImSchG (German Federal Immission Control)						<b>GRANER + PARTNER</b> I N G E N I E U R E Raumakustik Tontechnik Bauphysik Schallschutz 51465 Bergisch Gladbach																																																																																																															
date: 30.08.2010 Compiled by: Dipl. Ing. U. Gräf																																																																																																																					