



Nex Flex F22 LED | Flexible strip luminaire

horizontally or vertically bendable versions or with high output




Informations


- also suitable for outdoor use
- max. length with single-sided feed:
10 m (12 W/m), bzw. 8 m (15 W/m)
- max. length with 2-sided feed:
20 m (12 W/m), bzw. 16 m (15 W/m)
- dimmable
- UV-resistant (PVC)
- bendable up to 150 mm radius
- further variants (TW, RGB, RGBW, IP68, ...) on request



12 W/m, 15 W/m
400 - 800 lm/m
108 LED/m
2700 K, 3000 K
Beam angle: 160°
50'000h L70
CRI 80
Cutting unit: 55.6 mm




Version	Colour temperature	Power	Luminous flux	Article No.
horizontally bendable	2700 K	12 W/m	400 lm/m	120-006-20
horizontally bendable	3000 K	12 W/m	400 lm/m	120-006-70
vertically bendable	2700 K	15 W/m	800 lm/m	120-006-23
vertically bendable	3000 K	15 W/m	800 lm/m	120-006-73



Feeding

IP67


Version	Article No.
horizontal	120-006-90
vertical	120-006-91



End Cap

IP67


Version	Article No.
horizontal	120-006-88
vertical	120-006-89



Mounting profile

aluminium, Self-locking

Length	Article No.
35 mm	120-006-98



Mounting profile

aluminium, Self-locking

Length	Article No.
2000 mm	120-006-99