



Surface luminaire with IP54

**MODUS KX 2000, 600mm, LED 830, opal cover, surface, not dimable, 700mA**

**Code:** KX2000S3KO/ND

**EAN:** 8596099033033



## Vlastnosti svítidla

Product category:	<b>Ceiling / wall luminaires</b>	Degree of protection (IP):	<b>IP54</b>
Color housing:	<b>White</b>	Suitable for suspended mounting:	<b>Yes</b>
Material housing:	<b>Steel</b>	Suitable for wall mounting:	<b>Yes</b>
Suitable for surface mounting:	<b>Yes</b>	Suitable for ceiling mounting:	<b>Yes</b>
Made in Czech republic:	<b>Yes</b>		

## Světelný zdroj

Lamp type:	<b>LED exchangeable</b>	Effective luminous flux (lm):	<b>2500</b>
System power (W):	<b>20</b>	Luminaire efficacy (lm/W):	<b>125</b>
Color temperature (K):	<b>3000</b>	Color rendering index CRI:	<b>80-89</b>
Rated life time L80/B50 (h):	<b>80000</b>	With lamp:	<b>Yes</b>
Colour of light:	<b>White</b>		
Replaceability:	<b>Replaceable light source by professional, replaceable ballast</b>		

## Optický systém

Optical system:	<b>KO</b>	Light outlet:	<b>Direct</b>
Light sharing:	<b>Symmetric</b>	Material cover:	<b>Plastic, opal</b>
Radiation angle:	<b>Extreme wide beam &gt;80°</b>		

## Rozměry

Length (mm):	<b>630</b>	Width (mm):	<b>110</b>
Height/depth (mm):	<b>60</b>	Built-in length (mm):	<b>498</b>
Size version:	<b>S</b>	Weight (kg):	<b>1,5</b>

## Elektrické vlastnosti

Protection class:	<b>I</b>	Connection type:	<b>Pinching contact</b>
Voltage type:	<b>AC</b>	Type of control gear:	<b>LED operating device current-controlled</b>
Nominal voltage (V):	<b>220...240</b>	Control gear included:	<b>Yes</b>
No dim function:	<b>Yes</b>		