

UP¹ flush-mounting boxes



UP¹ ECON® Fix one-gang box

- More volume than conventional one-gang boxes
- With quick fixing for installation without plaster
- With 4 x 3 screw domes
- Side-neutral combination
- Many through-wiring possibilities
- Standardised combination distance 71 mm

| | |
|--------------------------------------------------------------------|----------------|
| Article no: | 1055-26 |
| EAN: | 4013456587427 |
| Depth | 46 mm |
| Drill hole Ø | 82 mm |
| With depth stop | Yes |
| With quick-fixing (also suitable for PU foam) | Yes |
| Screw spacing | 60 mm |
| Number of screw domes | 4 x 3 |
| Tool-free line and pipe entries in the combination range up to M25 | 2 |
| Toolless line and pipe entries up to M25 on the box circumference | 4 |
| Toolless cable entries up to Ø 11 mm in the bottom of the box | 2 |
| Toolless pipe entries up to M25 in the box bottom | 2 |
| Halogen-free | Yes |
| Air-tight | Yes |
| Packaging inner/dispatch | 25/250 |

UP¹, the new flush-mounting range for electrical installation, takes flush-mounting installation to a new level and makes it easier than ever before. 25% more installation volume compared to conventional flush-mounting one-gang junction boxes enables convenient accommodation of cables, connection terminals and installation accessories. The quick-fixing by means of ribs in all stones ensures up to 50% time savings during installation without plaster. The side-neutral and stable combination quickly allows multiple combinations to be created at a 71 mm centre distance. Thanks to open through-wiring and breakaway bridge, the device connection can be made without spatial separation. Accessories that are already wired, especially sockets, can therefore be installed particularly quickly and easily. The entries close to the base and through-wiring close to the base maximise the usable wiring space and facilitate the installation of the installation accessory due to the low-lying wiring material. Thanks to expanding claw fields and 4 x 3-fold screw domes, fixing the accessory is easier and more flexible than ever before. The new plaster compensation frame enables continuous plaster compensation from 10 to 35 mm with only one accessory.

- 25% more volume compared to conventional flush-mounted one-gang junction boxes
- Quick mounting in all wall constructions (ribs on the box, no mounting of accessories, use of PU foam is possible)
- Stable and side-neutral combination
- Open / diverse through-wiring
- Fully insulated through-wiring close to the base for deep boxes
- Entries close to the bottom of the box
- Triple conduit feed M25 from one direction to one-gang and one-gang junction boxes
- ECON® multi-cable conduit entries
- 4 triple screw domes / expanding claw fields
- Entries in the bottom of the box
- Stepless plaster compensation (accessories)

