

Fire-protection box HWD 68+



HWD 68+ one-gang box

- For F30-F90 or EI30-EI90, F30-B to F90-B fire-protection walls
- also for directly opposing installation
- from wall thicknesses of 100 mm
- can be combined with each other and with the one-gang junction box

Article no:	9463-03
EAN:	4013456578593
Depth	49 mm
For panel thicknesses up to	7 - 40 mm
Cut hole Ø	68 mm
Screw spacing	60 mm
Support connectors for each package	5
DIBt approval	Z-19.21-2693
ETA approval	ETA-22/0129
for sound insulation walls up to	69 dB
Conduit entries up to Ø 13 mm	6
Tube entries up to M25	2
Halogen-free	Yes
Packaging inner/dispatch	10/100

The new generation of KAISER fire protection boxes combine all the features of the HWD 68 and HWD 90. In addition, they cover all possible applications that occur in practice with the conduit entries. Thanks to the evaluated AFS technology, the HWD 68+ also guarantees a fire resistance duration of F30-F90 or EI30-EI90. The HWD 68+ also fulfils the F30-B-F90-B fire resistance duration in timber frame and timber panel construction as well as in cross-laminated timber construction. The HWD 68+ enables almost unrestricted and universal electrical installation in fire protection walls.

- For F30-F90 or EI30-EI90, F30-B to F90-B fire-protection walls
- Maintains the wall's sound insulation protection
- Toolless cable and conduit entry
- For installation openings Ø 68 mm
- For a directly opposing installation
- With fire-protection cover, can be used as a junction box

