

80 000

L80B50

CRI

80+

DALI

CCT

3000K

Technical sheet

Pendant/surface louvre fitting

MODUS AREL4000, 2x LED, 1245mm, mat AL louvre , ceiling/pendant, LED 830, 350mA DALI, white RAL9003

Code: AREL4000RM2KVM3DALI/9003 EAN: 8596099050252

Luminaire properties

• •			
Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	4400
System power (W):	37	Luminaire efficacy (lm/W):	119
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP20
Color housing:	White	Suitable for suspended mounting:	Yes
Material housing:	Steel		
Light source included:	Yes		
Suitable for surface mounting:	Yes	Suitable for ceiling mounting:	Yes
Made in Czech republic:	Yes		
Light source			
Light source type:	LED	Color temperature (K):	3000
Color rendering index CRI:	80-89	Replaceability:	Removeable light source, replaceable ballast
Optical system			
Optical system:	KVM	Light outlet:	Direct
Type of grid:	Matt	Anti-glare limiting UGR:	19
Light sharing:	Symmetric	Fit for monitor workplace:	Yes
Dimensions			
Length (mm):	1245	Width (mm):	245
Height/depth (mm):	55	Weight (kg):	4
Electrical values			
Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220240	Control gear included:	Yes
Type of wiring:	Suitable for through wiring	Dimming DALI:	Yes

UGR 220 v <19 50-60 Hz

占

(±)

IP 20